



# RATINGS CHART – GAS BOILERS

## LYNX COMBI

**Modulating, Condensing - High Efficiency  
with Domestic Hot Water Generator**

| SPECIFICATIONS                              |      | BOILER MODEL                         |                     |
|---|------|--------------------------------------|---------------------|
|   |      | LX-120CB                             | LX-150CB            |
| Input Rate, Btu/Hr                          | Max. | 120,000                              | 150,000             |
|   | Min  | 30,000                               | 37,500              |
| DHW Flow Rate at 60°F Temperature rise, GPM |      | 3.5                                  | 4.5                 |
| Water Piping Connection                     |      | 1" NPT (Male)                        |                     |
| Gas Piping Connection                       |      | 1/2" NPT (Female)                    |                     |
| DHW (Cold In and Hot Out Connection)        |      | 3/4" Nom. ID Copper Tube             |                     |
| Vent and Air Intake Connection              |      | 3" Nominal ID Pipe (PVC, CPVC or SS) |                     |
| Gas Orifice Size for Natural Gas            |      | No Orifice Used                      |                     |
| Gas Orifice Size for Propane                |      | 0.2025"<br>Code # A                  | 0.2200"<br>Code # E |
| Boiler Water Volume                         | Gal. | 0.6                                  | 1.1                 |
| Weight of Boiler (Uncrated)                 | Lbs. | 147                                  | 162                 |

